

Özellikler:

600 (to) 75°C 90°C

Özellikler:

6201 ASTM-B-399 ACSR 6/1

75°C 40°C

:

Özellikler: (info@himakecable.com)

(ACSR)

	(AWG)	mm)	(AWG)		(mm)	
Paludina	6-6/1	1.14	6-6/1	540	170	79
Voluta	6-7	1.14	6-6/1	540	176	79
Bolma	6-7	1.52	6-6/1	540	194	79
	4-6/1	1.14	66/1	540	225	138
Strombus	4-7	1.14	6-6/1	540	232	138
	4-7	1.52	6-6/1	540	253	138
	4-6/1	1.14	4-6/1	844	258	138
	4-7	1.14	4-6/1	844	263	138
	4-7	1.52	4-6/1	844	284	138
	2-7	1.14	4-6/1	844	335	183

Özellikler:

- 1.



2. ආවරණ ආවරණයක් ආවරණයක් අවුරුදුව පුනරාවරණය කළ විට ආවරණයක් අවුරුදුව පුනරාවරණය කළ විට

ආවරණ



□□□□□□



3. 10 international 60





4. 圖中展示了電纜生產廠的生產、倉儲、裝載及運輸過程。圖中展示了電纜生產廠的生產、倉儲、裝載及運輸過程。



5. 責任感 responsibility



