

特長:



規格: 国際規格 IEC 60332-1 1350 H19 対応

外皮: PE 高耐候性樹脂 採用

導体: 鋼絞線 AAC、ACSR、AAAC 鋼絞線 鋼絞線 鋼絞線 6201 鋼絞線 鋼絞線 鋼絞線

構造: 鋼絞線 鋼絞線-鋼絞線

用途: 鋼絞線 鋼絞線 鋼絞線

規格: ASTM B 230 B-231、B-232 B-399、IEC S-76-474

特徴:

鋼絞線 鋼絞線 鋼絞線 120 鋼絞線 鋼絞線 鋼絞線 600 鋼絞線 鋼絞線 75℃ 鋼絞線

6201 ASTM B 399 ACSR 6/1

75°C 40°C

500

(ACSR

	AWG	(mm)	AWG	(kg)	(kg/km)	(A)
	6	1.14	6-6/01	540	94	78
	6-7	1.14	6-6/01	540	97	78
	6-7	1.52	6-6/01	540	106	78
	4	1.14	4-6/01	844	141	103
	4-7	1.14	4-6/01	844	146	103
Yorkshirc	4-7	1.52	4-6/01	844	156	103
	2-7	1.14	2-6/01	1293	223	136
	1-19	1.52	1-6/01	1610	290	158
	1/0-7	1.52	1/0-6/01	1987	359	182
	1/0-19	1.52	1/0-6/01	1987	359	182

1.



□□□□□□□□



3. 10 60 internationally





5월 10일 10시 30분부터 12시 30분까지



10월 10일 10시 30분부터 12시 30분까지

10월 10일 10시 30분부터 12시 30분까지

