

□□□□□:



□□□□: 0.6/1 KV

□□: □□□ 2 □□□□□□□□□□□□□□

□□□□□□□: 1.5sqmm □ 2.5sqmm

規格: 2 C ~ 50 C + E

材質: V-90 PVC

構成: 導体 絶縁体 + 保護層 + 保護層

標準規格 (規格): 国際規格

電圧: 5 V 90

用途: 各種用途

Max 長さ 90

仕様: 各種仕様

標準規格: 各種規格

規格: AS/NZS5000.1

特徴:

環境にやさしい (RoHS) 対応製品。無鉛ロハンズ (lead-free) 対応製品。

仕様:

標準規格: 各種規格 (unarmored) 対応製品。

お問い合わせ: (お問い合わせ先: info@himakecable.com)

導体積 (mm ²)	導体径 (mm)	外径 (mm)	重量 (kg/km)
5 × 1.5 + E	7/0.50	13.1	220
6 × 1.5 + E	7/0.50	13.1	240
8 × 1.5 + E	7/0.50	15.4	300

お問い合わせ:

1. □□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□



2. 下列各题中，每题有四个选项，其中只有一个选项是正确的。请将正确答案的序号填入题后的括号内。

1. ()



□□□□□□



3. 10 60 internationally SAA





