

□□□□:

□□□□: 300/300 V

□□: □□ 5 □□□□□□□□□□

□□□□□□: 0.3 □ 1.0sqmm□□□□□□□□□□ 16sqmm □□□□□□□□□□ □□

□□□: □□□□□□□□ PVC Rohs □□ PVC

□□□□□: □ + □□□ + □□□□□ □□□□ □□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□

**Max**□□□□□□□ 70□90

□□□□□: 100 □□□□□□□□□□□□□□

□□□□□□□: RVB□H03VH F□H05VH F□□ 8 □□□□□

Standards: IEC60277 BS6500 VDE0281 GB/T IEC60332 5023

**Product Name:**

Product description: ... rohs ...

**Product Code:**

Product details: ...

**Contact Information:** (Email: info@himakecable.com)

Cable Size (mm <sup>2</sup> )	Insulation (mm)	Core av (mm)	Max. Resistance at 20°C (Ω/km)		Resistance at 70°C (mΩ·km)
			DC	AC	
2 × 0.3	PVC/0.6	2.1 × 03.9	69.2	71.2	0.016
2 × 0.4	PVC/0.6	2.2 × 04.3	48.6	49.6	0.014
2 × 0.5	PVC/0.6	2.7 × 05.3	39	40.1	0.016
2 × 0.75	PVC/0.8	2.9 × 05.7	26	26.7	0.014
2 × 1.0	PVC/0.8	3.1 × 06.1	20	20	0.012

**Notes:**

1. Product details ...







□□□□□□



3. 10 60 internationally







4. 〇〇〇〇〇〇〇〇〇〇〇〇 〇〇〇〇 〇 〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇





