



**Max** 70x90x105

Length: 100 m

Model: KVV22ZR KVV22

Standards: IEC60277 BS6500 VDE0250 GB/T9330 IEC60332

**Features:**

RoHS compliant

**Applications:**

General purpose power cables for industrial and commercial applications.

**Technical Specifications (450/750 v):**

Contact: info@himakecable.com

Cable Size (mm <sup>2</sup> )	Conductor (mm)		Insulation (mm)		Overall (mm)		Weight (kg/km)	
	450/750 V	0.6/1 KV	450/750 V	0.6/1 KV	450/750 V	0.6/1 KV	450/750 V	0.6/1 KV
2 x 4	PVC/0.8	PVC/1.0	PVC/1.5	PVC/1.8	16.9	18.3	656	725
2 x 6	PVC/0.8	PVC/1.0	PVC/1.5	PVC/1.8	17.9	19.3	744	816
2 x 10	PVC/1.0	PVC/1.0	PVC/1.7	PVC/1.8	21.7	21.9	1019	1028
3 x 2.5	PVC/0.8	PVC/0.8	PVC/1.5	PVC/1.8	16.5	17.1	634	657
3 x 4	PVC/0.8	PVC/1.0	PVC/1.5	PVC/1.8	17.5	19	727	803

**Notes:**

1. All dimensions are in millimeters unless otherwise specified.











□□□□□□







3. 10 60 internationally



















