

□□□□□:



□□□□: 450/750 V □0.6/1 KV

□□: □□□□ □□ 1 □□□□□□ 2 □□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□: 0.75 ~ 10sqmm

□□□□: □□□□□□□□ PVC Rohs □□□□

□□□□□□: □□□□□□□□□□ 5 □□ □□□□□□□□ 5 □□□□□□□□□□□□ □

□□□□□□□□□□□□□□□□□□□□□□: □□□□

□□: □□□□□□□□ PVC Rohs □□□□

□□□□□□: □□□□□□□□□□□□□□□□

Max 70x90x105

Length: 100 m

Material: KVV32 ZR KVV32

Standards: IEC60277 BS6500 VDE0250 GB/T9330 IEC60332

Features:

RoHS compliant

Applications:

General purpose

Specifications (450/750 v):

Contact: info@himakecable.com

Cable Size (mm ²)	Conductor (mm)		Insulation (mm)		Overall (mm)		Weight (kg/km)	
	450/750 V	0.6/1 KV	450/750 V	0.6/1 KV	450/750 V	0.6/1 KV	450/750 V	0.6/1 KV
2 x 4	PVC/0.8	PVC/1.0	PVC/1.5	PVC/1.8	16.9	18.3	656	725
2 x 6	PVC/0.8	PVC/1.0	PVC/1.5	PVC/1.8	17.9	19.3	744	816
2 x 10	PVC/1.0	PVC/1.0	PVC/1.7	PVC/1.8	21.7	21.9	1019	1028
3 x 2.5	PVC/0.8	PVC/0.8	PVC/1.5	PVC/1.8	16.5	17.1	634	657
3 x 4	PVC/0.8	PVC/1.0	PVC/1.5	PVC/1.8	17.5	19	727	803

Notes:

1. General purpose



2 下列各题中，() 是方程 $x^2 - 2x + 1 = 0$ 的根。

()



□□□□□□



3. 10 60 internationally







