

□□□□□:



□□□□: 450/750v

□□: □□□1□□□□□□□□□□□□2□□□□□□□□□□□□□□□5 □□□□□□□□□□□□□□□□

□□□□□□□□: 0.75 ~ 10sqmm

□□: pvc□□□□□ pvc□rohs □□ pvc

规格: 5芯 PVC 护套 5芯 PVC 绝缘

材料: PVC 护套 PVC 绝缘 PVC 芯

颜色: 黑色

工作温度: 70°C, 90 °C

长度: 100米 定制长度

认证: KVV KVVR YY

标准: IEC60277 BS6500 VDE0250 GB/T9330 IEC60332

特性:

符合 RoHS 环保标准

规格表:

规格表详细描述了不同芯数和护套厚度的电缆特性

规格表 (450/750v):

(联系邮箱: info@himakecable.com)

规格 mm ²)	护套 mm)	绝缘 mm)	导体 mm)	重量 (g/m)	电阻 (ω /km)	电容 (m ω • km)
2x 0.75	pvc/0.6	pvc/1.2	7.5	67.72	24.5	0.012
2x 1.0	pvc/0.6	pvc/1.2	7.82	76.2	18.1	0.011
2x 1.5	pvc/0.7	pvc/1.2	8.74	97.71	12.1	0.011
2x 2.5	pvc/0.8	pvc/1.2	9.96	133.4	7.41	0.01
2x4	pvc/0.8	pvc/1.2	10.9	173.65	4.61	0.0085

应用:

1. 适用于各种工业控制线路



2. 下列各句，其句意與「此其所以為國也」最接近者為：

(A) 此其所以為國也



□□□□□□



3. 10 60







5. 責任感 responsibility



