

□□□□:



□□□□: 450/750 V

□□: □□ 1 □□□□□□ 2 □□□□□□□□ □□□□□□□□

□□□□□□□□: 1.0 □ 16sqmm

□□: 2 C□3 C□2 C + E□3 C + E

□□□: V-90 PVC

□□□□□□: 2 C: □ + □□□□□□ + □□2 C + E: □ + □ + □/□□□3 C: □ + □ + □□3 C + E: □ + □ + □ + □/□

□: 3 V 90 □□

□□□□□□: □□□□□□□□□□□□

Max□□□□□□ 90

□□□□□□: 100 m □□ (□□□□□□□□ □□□□□□□□□□ □□

□□□□□□□□: PVC □□□□ TP □□□□□□□□□□□□□□ □□□□ □□□ □□□□□□□□ □□□□□□ PVC □□□□ □□□□

標準: AS/NZS5000.2

特徴:

標準規格に準拠し、環境に優しい材料を使用し、RoHS 規格に適合しています。

仕様:

標準規格、環境に優しい材料を使用し、RoHS 規格に適合しています。

お問い合わせ: (お問い合わせ先: info@himakecable.com)

断面積 (mm ²)	材料	外径 (mm)	内径 (mm)	重量 (mm ²)	外径 (mm)	重量 (kg/km)
2 × 1.0	Cu	0.6	0.9	/	6.5 × 4.2	50.4
2 × 1.5	Cu	0.6	0.9	/	7.2 × 4.5	61.7
2 × 2.5	Cu	0.7	1.0	/	8.9 × 5.4	96.8
2 × 4.0	Cu	0.8	1.1	/	10.5 × 6.3	141.9
2 × 6.0	Cu	0.8	1.1	/	11.6 × 6.9	185.9
2 × 10	Cu	1.0	1.2	/	14.2 × 8.3	294.2

お問い合わせ:

- お問い合わせ先: info@himakecable.com





□□□□□□



3. 10 60 internationally







