

□□□□□:



□□□□: 300/500 V □ 450/750 V

□□: □□ 5 □□□□□□□□

□□□□□□: 0.5 □ 240sqmm

□□□: XLPE LSZH □ LSOH

□□□□□: □□□□□□□□□□□□□□ □□□□□□□□□□/□□□□□□□□□□

Max□□□□□□ 90, 110, 125°C, 150

□□□□□: 100 m □□□□□□□□□□□□□□ □□

□□□□□□□: BS7211 2491B/6401B H07Z K H05Z K □ WDZ RYJ RJY

□□□□□: BS7211 IEC60332 □ IEC61034 □ IEC60754 □ VDE0282

品名:

本公司 製造之電線電纜均符合 CE 認證及 ISO 9001 認證，並符合 RoHS 指令之要求。

規格說明:

本公司電線電纜之規格均符合 IEC 60332-1 及 IEC 60332-2 之要求。

查詢電話: (電子郵件地址: info@himakecable.com)

線徑 (mm ²)	股數	絕緣 厚度 (mm)	Max 線徑 (mm)	重量 (kg/km)	電阻 (MΩ.km)
0.5	5	PVC/0.6	2.4	8.34	0.013
0.75	5	PVC/0.6	2.6	11.08	0.011
1	5	PVC/0.6	2.8	13.73	0.01
1.5	5	PVC/0.7	3.5	19.94	0.01
2.5	5	PVC/0.8	4.2	30.95	0.009
4	5	PVC/0.8	4.8	46.8	0.007
6	5	PVC/0.8	6.3	67.82	0.006

備註:

- 本公司電線電纜之規格均符合 IEC 60332-1 及 IEC 60332-2 之要求。





□□□□□□



3. 10 60 internationally





4. 臺灣電線電纜有限公司 電線 電纜 電力電纜 電訊電纜 電力電纜及電訊電纜 電力電纜及電訊電纜 電力電纜及電訊電纜



