

□□□□□:



□□□□: 300/500 V □ 450/750 V

□□: □□ 5 □□□□□□□□

□□□□□□: 0.5 □ 240sqmm

□□□: Rohs □□ PVC □□□□

□□□□□: □□□□□□□□□□□□□□ □□□□□□□□□□/□□□□□□□□□□

Max□□□□□□ 70□90

□□□□□: 100 m □□□□□□□□□□□□□□ □□

□□□□□□□: H07V-K H05V K ZR-RV □RV

□□□□: IEC60277 □BS6500 VDE0281 GB/T IEC60332 5023

ชื่อ:

ข้อมูลผลิตภัณฑ์: ข้อมูลผลิตภัณฑ์: ข้อมูลผลิตภัณฑ์: rohs ข้อมูล ผลิตภัณฑ์

คุณสมบัติ:

ข้อมูลผลิตภัณฑ์: ข้อมูลผลิตภัณฑ์: ข้อมูลผลิตภัณฑ์

ติดต่อ: (อีเมล: info@himakecable.com)

ขนาด เส้น (mm ²)	จำนวน เส้น	ขนาด เส้น (mm)	Max (mm)	น้ำหนัก (kg/km)	ความต้านทาน (MΩ.km)
0.5	5	PVC/0.6	2.4	8.34	0.013
0.75	5	PVC/0.6	2.6	11.08	0.011
1	5	PVC/0.6	2.8	13.73	0.01
1.5	5	PVC/0.7	3.5	19.94	0.01
2.5	5	PVC/0.8	4.2	30.95	0.009
4	5	PVC/0.8	4.8	46.8	0.007
6	5	PVC/0.8	6.3	67.82	0.006

หมายเหตุ:

1. ข้อมูลผลิตภัณฑ์: ข้อมูลผลิตภัณฑ์: ข้อมูลผลิตภัณฑ์



2 下列各句，没有语病的一项是（ ）



□□□□□□



3. 10 60 internationally





