

□□□□□:



www.himakecable.com
info@himakecable.com

□□□□: 1.0 □ 16sqmm 450/750 v □25 □ 630sqmm 0.6/1 kv

□□: □□ 1 □□□□□□ 2 □□□□□□□□ □□□□□□□□

□□□□□□□□: 1.0 □ 630sqmm

□□□: V-90 PVC

□□□□□□: □□□□□□□□□□□□

□: 3 V 90 □□

□□□□□□: □□□□□□□□□□□□

Max□□□□□□ 90

□□□□□□: 100 m □□ (□□□□□□□□ □□□)□□□□□□□□□□ □□

Material: PVC SDI

Dimensions: 1.0 mm² 16sqmm Voltage: 450/750 v/NZS5000.2 25 mm² 630sqmm Voltage: 0.6/1 kv/NZS 5000.1

Properties:

Material: PVC SDI, Conductor: Copper, Insulation: PVC SDI, RoHS: Compliant

Technical Specifications:

Technical specifications and performance characteristics of the cable are detailed in the accompanying technical data sheet.

Contact Information: (Email: info@himakecable.com)

Conductor Area (mm ²)	Conductor Material	Conductor Diameter (mm)	Insulation Thickness (mm)	Max. Cable Diameter (mm)	Weight (kg/km)
1 x 1.0	Copper (Cu)	0.6	0.8	4.0	27
1 x 1.5	Copper (Cu)	0.6	0.8	4.4	32
1 x 2.5	Copper (Cu)	0.7	0.8	5.1	48
1 x 4.0	Copper (Cu)	0.8	0.9	6.0	71
1 x 6.0	Copper (Cu)	0.8	0.9	6.6	94
1 x 10	Copper (Cu)	1.0	0.9	7.8	143
1 x 16	Copper (Cu)	1.0	1.0	8.9	208
1 x 25	Copper (Cu)	1.2	1.4	11.1	323

Notes:

1. All dimensions are in millimeters unless otherwise specified.





□□□□□□



3. 10 60 internationally







