





NYA PVC 300/500V 450/750V

300/500V 450/750V

2

0.75 400mm

PVC PVC

70°C 90°C 105°C

1 100

NYA FR-NYA BV BVR H05V-R H07V-R BS6004 6491X

IEC60277 BS6004 VDE0250 GB/T 5023

RoHS

RoHS

RoHS

fo@ himake

规格	材料	厚度	重量	70°C 电阻率 (MΩ·km)	重量 (kg/km)
1×0.75	PVC/0.6	2.8	0.014	11.8	
1×1.0	PVC/0.6	3.0	0.013	14.3	
1×1.5	PVC/0.7	3.4	0.010	21.3	
1×2.5	PVC/0.8	4.2	0.009	34.4	
1×4.0	PVC/0.8	4.8	0.0077	47.0	
1×6.0	PVC/0.8	5.4	0.0065	68.7	
1×10	PVC/1.0	6.8	0.0065	116	
1×16	PVC/1.0	8.0	0.0050	168	
1×25	PVC/1.2	9.8	0.0050	275	
1×35	PVC/1.2	11	0.0040	372	
1×50	PVC/1.4	13	0.0045	503	
1×70	PVC/1.4	15.0	0.0035	708	
1×95	PVC/1.6	17.2	0.0035	979	
1×120	PVC/1.6	19.0	0.0032	1207	
1×150	PVC/1.8	21.0	0.0032	1493	
1×185	PVC/2.0	23.5	0.0032	1861	
1×240	PVC/2.2	26.5	0.0032	2437	
1×300	PVC/2.4	29.5	0.0030	3066	
1×400	PVC/2.6	33.5	0.0028	3895	

1.

1. 规格





□□□□□□□□



3. 15 60 international







5. 5월 10일(수) 10:00 ~ 11:30 (1시간 30분) 5월 10일(수) 10:00 ~ 11:30 (1시간 30분)



