

□□□□□:



□□□□: 300/500 V □ 450/750 V

□□: □□ 1 □□□□□□ 2 □□□□□□□□ □□□

□□□□□□□□: 0.5 □ 10sqmm

□□□□: □□ PVC □□□□□

□□□□□□: □□□□□□□□□□□□□□□□ □□□□□□□□□□/□□□□□□□□□□□□

**Max**□□□□□□□ 70□90□105

□□□□□□: 100 m □□□□□□□□□□□□□□ □□

□□□□□□□□: BS6004 □ H05V U BLVR BLV BV 6491 X

□□□□□□: IEC60277 □ BS6004 □ VDE0281 GB/T 5023

**概要:**

本製品は環境にやさしい材料を使用し、rohs 対応製品です。

**仕様:**

本製品は、標準的な仕様で提供されます。詳細な仕様についてはお問い合わせください。

**お問い合わせ:** (お問い合わせ先: info@himakecable.com)

断面積 (mm <sup>2</sup> )	規格	外径 (mm)	Max外径 (mm)	70℃ 絶縁抵抗 (MΩ・km)	重量 (kg/km)
1 × 0.5	規格 1 対応品	PVC/0.6	2.4	0.015	8.1
1 × 0.75	規格 1 対応品	PVC/0.6	2.6	0.012	10.9
1 × 1.0	規格 1 対応品	PVC/0.6	2.8	0.011	13.7
1 × 1.5	規格 1 対応品	PVC/0.7	3.3	0.011	20.0
1 × 2.5	規格 1 対応品	PVC/0.8	3.9	0.010	31.1
1 × 4.0	規格 1 対応品	PVC/0.8	4.4	0.0085	45.7
1 × 6.0	規格 1 対応品	PVC/0.8	4.9	0.0070	65.2
1 × 10	規格 1 対応品	PVC/1.0	6.4	0.0070	112

**注意事項:**

- 本製品は、特定の用途にのみ使用してください。









□□□□□□



3. 10 60 internationally











