

产品特点:



- 电压: 300/500 V 450/750 V
- 导体: 单股/双股
- 截面: 0.75 ~ 400sqmm
- 绝缘: PVC 绝缘
- 用途: 适用于室内布线/室外布线
- Max** 导体长度 70 90 105
- 颜色: 黄色/绿色/蓝色/红色 长度 100 m
- 标准: BS6004 H07V-R H05V R BVR 6491 X
- 认证: IEC60277 BS6004 VDE0281 GB/T 5023

环境:

符合欧洲环保要求，不含铅、镉、汞、铬、卤素，符合 rohs 环保标准。

服务支持:

我们提供完善的售后服务，包括产品咨询、技术支持、安装调试、故障排查、配件供应等。

हिमाकेबल्स प्राइवेट लिमिटेड: (दूरस्थ सूचना के लिए: info@himakecable.com)

विद्युत क्षेत्रफल (mm ²)	संरचना	बिनामी (mm)	Max बिनामी (mm)	70 बिनामी (MΩ·km)	भार (kg/km)
1 x 0.75	2 बिनामी	PVC/0.6	2.8	0.014	11.8
1 x 1.0	2 बिनामी	PVC/0.6	3.0	0.013	14.3
1 x 1.5	2 बिनामी	PVC/0.7	3.4	0.010	21.3
1 x 2.5	2 बिनामी	PVC/0.8	4.2	0.009	34.4
1 x 4.0	2 बिनामी	PVC/0.8	4.8	0.0077	47.0
1 x 6.0	2 बिनामी	PVC/0.8	5.4	0.0065	68.7
1 x 10	2 बिनामी	PVC/1.0	6.8	0.0065	116
1 x 16	2 बिनामी	PVC/1.0	8.0	0.0050	168
1 x 25	2 बिनामी	PVC/1.2	9.8	0.0050	275
1 x 35	2 बिनामी	PVC/1.2	11	0.0040	372
1 x 50	2 बिनामी	PVC/1.4	13	0.0045	503
1 x 70	2 बिनामी	PVC/1.4	15.0	0.0035	708
1 x 95	2 बिनामी	PVC/1.6	17.2	0.0035	979
1 x 120	2 बिनामी	PVC/1.6	19.0	0.0032	1207
1 x 150	2 बिनामी	PVC/1.8	21.0	0.0032	1493
1 x 185	2 बिनामी	PVC/2.0	23.5	0.0032	1861
1 x 240	2 बिनामी	PVC/2.2	26.5	0.0032	2437
1 x 300	2 बिनामी	PVC/2.4	29.5	0.0030	3066
1 x 400	2 बिनामी	PVC/2.6	33.5	0.0028	3895

सूचना:

1. विद्युत क्षेत्रफल बिनामी के अनुसार बदल सकता है



2 下列各题中，选择正确的答案。

（ ）



□□□□□□



3. 10 60 internationally







4. [REDACTED]



5. 2014年 5月 10日 在 北京 市 房 山 区 大 石 门 山 公 园 举 行 的 植 树 活 动



2014年 5月 10日

在 北京 市 房 山 区 大 石 门 山 公 园 举 行 的 植 树 活 动 中 ， 我 们 参 与 了 植 树 活 动 ， 培 植 了 许 多 小 树 苗 ， 为 环 境 保 护 贡 献 了 一 份 力 量 。

