

□□□□□:

海迈电缆
Himake Cable

Copper Conductor

XLPE Insulation

5V-90 PVC Sheath

www.himakecable.com
info@himakecable.com

CCC CE SAA UL CB R&HS

□□□□: 0.6/1 KV

□□: □□ 2 □□□□□□□□□□□□□□

□□□□□□□: 16 ~ 630sqmm

□□□: V-90 PVC

□□□□□: □□□□□□□□□□□□

□: 5 V 90 □□

□□□□□: □□□□□□□□□□

Max□□□□□□ 90

□□□□□: 100 m □□ (□□□□□□ □□□)□□□□□□□□□□ □□

Material: XLPE SDI

Standard: AS/NZS 5000.1

Color:

Material is compliant with RoHS (Restriction of Hazardous Substances)

Dimensions:

Dimensions are given in millimeters (mm) unless otherwise specified.

Contact: (Email: info@himakecable.com)

Area (mm ²)	Outer Diameter (mm)	Inner Diameter (mm)	Max. Length (mm)	Weight (kg/km)
1 x 16	0.8	1.4	9.3	210
1 x 25	0.9	1.4	10.5	300
1 x 35	0.9	1.4	11.5	400
1 x 50	1.0	1.4	12.9	520
1 x 70	1.1	1.4	14.7	730
1 x 95	1.1	1.5	17.2	1010
1 x 120	1.2	1.5	19.6	1230
1 x 150	1.4	1.6	21.3	1520

Notes:

1. Dimensions are given in millimeters (mm) unless otherwise specified.





□□□□□□



3. 10 60 internationally







4. 〇〇〇〇〇〇〇〇〇〇〇 〇〇〇〇 〇 〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇



