

□□□□□:



□□□□: 0.6/1 KV

□□: □□□□ □□ 1 □□□□□□ 2 □□□□□□□□□□□□ □

□□□□□□□: 1.5 □ 1000sqmm

□□□: LSZH□□□□□□□□□□PE LSOH

□□□□□: 2 C: □ + □□3 C: □ + □□ + □□4 C: □ + □□ + □ + □□5 C: □ + □□ + □ + □□□□ + □□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□: LSZH□PE LSOH

□□□□□: □□□□□□□□□□

Max□□□□□□□ 90, 110, 125°C, 150

Model: YJY33-WDZ YJY33

Compliance: IEC60502-1 BS7870 VDE0276 GB/T12706 IEC60332

Cable Type: YJY33-WDZ YJY33

General Information:

The cable is designed for indoor and outdoor use, suitable for fixed and mobile applications. It complies with RoHS standards and is free from lead, mercury, and cadmium.

Technical Specifications:

The cable is constructed with XLPE insulation and PVC jacket. It is suitable for use in environments with high temperature and humidity. The cable is rated for 0.6/1 kV and is suitable for use in A/C systems.

Contact Information: (Email: info@himakecable.com)

Cable Structure (mm²)	XLPE Insulation (mm)	Conductor Diameter (mm)	PVC Jacket Thickness (mm)	Overall Diameter (mm)	Weight (Kg/Km)
16 + 10 x 3	0.7/0.7	1.25	1.7	23	1180
25 + 16 x 3	0.9/0.7	1.6	1.7	26.1	1750
35 + 16 x 3	0.9/0.7	1.6	1.8	27.9	2100
50 + 25 x 3	1.0/0.9	1.6	1.9	31.2	2750
70 + 35 x 3	1.1/0.9	2	2	36.6	3450
95 + 50 x 3	1.1/1.0	2	2.1	41	4900
120 + 70 x 3	1.2 1.1	2	2.2	45.3	6040
70 150 + x 3	1.4 1.1	2.5	2.4	50	7590
185 + 95 x 3	1.6 1.1	2.5	2.5	55.3	9130

Notes:

1. The cable is suitable for use in indoor and outdoor environments.



2. 下列各句，其句式與「此其所以見效也」相同者，請選出二項。

（1）夫豈易言哉！



□□□□□□



3. 10 60 internationally





5



.

