

□□□□:



□□□□: 300 V

□□: □□□□□□□□□□□□□□□□

□□□: PVC

□□□□□□□□□□ □□ □□□□□□□□□□□□□□

□□□□□: □□□□610 □□□□□□□□ 2000 □□□□ □□□□□□□□□□□□□□

□□□□: 80

□□: UL1007 UL758□UL1581□CSA22.2

UL 1007 PVC:

UL 1007 PVC 1 UL CSA FT1

UL 1007 PVC:

UL 1007 PVC

UL 1007 PVC: (Email: info@himakecable.com)

UL & CSA	AWG	Outer Diameter (mm)	Inner Diameter (mm)	Outer Diameter (mm)	-20°C Resistance (Ω/km)
UL1007 (Solid)	30	7/0.100	0.41	1.10	381.00
	28	7/0.127	0.41	1.20	239.00
	26	7/0.160	0.41	1.30	150.00
	24	11/0.160	0.41	1.40	94.20
	22	17/0.160	0.41	1.60	59.40
	20	21/0.178	0.41	1.80	36.70
UL1007 (Stranded)	26	7/0.160	0.41	1.30	140.00
	24	7/0.200	0.41	1.40	88.70
	22	7/0.250	0.41	1.60	54.70
UL1007 (Plenum)	26	1/0.404	0.41	1.25	143.00
	24	1/0.511	0.41	1.35	89.30
	22	1/0.634	0.41	1.50	56.40
	20	1/0.813	0.41	1.65	35.20

UL 1007 PVC:

1. UL 1007 PVC





□□□□□□



3. 10 60 internationally

 海迈电缆
Himake Cable



www.himakecable.com
info@himakecable.com



