

Nominal Voltage: 300/500V Conductor: Class 5 plain annealed fine copper wire Conductor nominal cross section area: 0.5~6.0sqmm Insulation: XLPE,LSZH, LSOH Insulation color: Blue, Brown, Grey, Black, red, Green/Yellow or other color requested Cores: 2~5 cores Sheath: LSZH, LSOH Sheath color: black, grey, white, or as per request Max. operating temperature: 90°C, 110°C, 125°C, 150°C Package: 100 meters per roll, or as per requirement Main product model: H05ZZ-F, H07ZZ-F

Product standard: BS7211, IEC60332, IEC61034, IEC60754, HD22.9, VDE0282, GB/T19666

### **Product characteristics:**

Low smoking halogen free, Very flexible for easy bending, high temperature resistance, low temperature resistance, flame retardant and high electrical conductivity, also fire resistance, UV resistance or Rohs compliant can be available as per request.

# **Product application:**

The cables are used for general power supply and distribution purpose, for switch control, instrumentation panels and for internal connection.

| conductor          | Kind      | Insulation | Sheath    | Average max.   | Product        | Min. insulated |
|--------------------|-----------|------------|-----------|----------------|----------------|----------------|
| cross-section      | Of        | thickness  | thickness | outer-diameter | approximate    | resistance     |
| (mm <sup>2</sup> ) | conductor | (mm)       | (mm)      | (mm)           | weight (kg/km) | (MΩ.km)        |
| 2×0.75             | 5         | PVC/0.6    | PVC/0.8   | 7.6            | 49.24          | 0.011          |
| 2×1                | 5         | PVC/0.6    | PVC/0.8   | 8              | 56.59          | 0.01           |
| 2×1.5              | 5         | PVC/0.7    | PVC/0.8   | 9              | 74.6           | 0.01           |
| 3×0.75             | 5         | PVC/0.6    | PVC/0.8   | 8              | 61.23          | 0.011          |
| 3×1                | 5         | PVC/0.6    | PVC/0.8   | 8.4            | 71.27          | 0.01           |
| 3×1.5              | 5         | PVC/0.7    | PVC/0.9   | 9.8            | 99.3           | 0.01           |
| 3×2.5              | 5         | PVC/0.8    | PVC/1.1   | 12             | 150.53         | 0.009          |
| 4×0.75             | 5         | PVC/0.6    | PVC/0.8   | 8.6            | 75.12          | 0.011          |
| 4×1                | 5         | PVC/0.6    | PVC/0.9   | 9.4            | 91.72          | 0.01           |
| 4×1.5              | 5         | PVC/0.7    | PVC/1.0   | 11             | 127.54         | 0.01           |
| 4×2.5              | 5         | PVC/0.8    | PVC/1.1   | 13             | 187.6          | 0.009          |

#### Product parameter: (more details please email us: info@himakecable.com )

# **Product Advantages:**

1. The conductor is made of **new pure annealed copper**, ensuring a good electrical properties and a very good conductivity.



2. We are a very **professional cable manufacturer** with advanced production equipments and strict quality inspection system, ensuring the products complying the standard and customized requirement.

## **Production equipments**















#### **Products Quality inspection equipments**



3. We have more than **10 years' export experience** and exported products to **more than 60 countries** over the world with a good reputation international ly.



4.We not only offer **good products** and **good service** to our customers, but also try to **develop our staffs**, offer a good trainning, good working and living conditions to the staffs.

5. Also we are a company with **highly social reponsibility**, often take part in public benifits activities, like tree planting, aiding poor students, green environment activities, etc.

