Kenmerken van het product

1. Multi één kabelontwerp
2. enkele kabel met onafhankelijke sterkte lid
3. 2 ~ 24 kernen
4. niet-metalen centrale kracht lid

Product toepassing

Aangenomen binnen niveau en verticale leggen, plafond leggen, oppervlakte leggen, enz. Geschikt voor patch snoeren en pigtails.

De parameter product (meer informatie kunt u mailen naar: info@himakecable.com)

Cstaat kern	Buitenste Verwarmingselement	Gewicht	Min. toegestane treksterkte (N)		Min. toegestane Crush belasting (N \/ 100mm)		Min. Buigen van Radius (mm)	
Graaf	(mm)	(kg\/km)	Korte termijn	Lange termijn	Korte termijn	Lange termijn	Korte termijn	Lange termijn
02	7.0	45	1500	500	1000	300	20D	10D
04	7.0	47	1500	500	1000	300	20D	10D
06	8.3	64	1500	500	1000	300	20D	10D
08	9.5	88	1500	500	1000	300	20D	10D
12	11,5	105	1500	500	1000	300	20D	10D
24	13,5	142	1500	500	1000	300	20D	10D

Productvoordelen

1. de dirigent is gemaakt van topkwaliteit optische vezels, het heeft lage dispersie en demping, ervoor moet zorgen dat een zeer goed signaal en data transmissie.

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.

Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing

APPLICATION

✔ Pipeline

✔ Overhead

✔ Direct bury

Packaging & Shipping

PACKING AND SHIPPING

- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.

info@himakecable.com