



Kenmerken van het product

1. hoge sterkte kevlar garen lid
2. meer strak gebufferde ontwerp
3. ronde bouw, zacht, makkelijk te strippen
4. 2 ~ 48 kernen
5. buitenste schede materiaal: PVC, PU, LSZH, OFNP

Product toepassing

Aangenomen naar binnen distributie, geschikt voor vloer verbinding, geschikt voor communicatieapparatuur.

De parameter product (meer informatie kunt u mailen naar: info@himakecable.com)

Kabel kern	Buitenste Verwarmingselement	Gewicht	Min. toegestane treksterkte (N)		Min. toegestane Crush belasting (N / 100mm)		Min. Buigen van Radius (mm)	
Graaf	(mm)	(kg/km)	Korte termijn	Lange termijn	Korte termijn	Lange termijn	Korte termijn	Lange termijn
02	3.0	15	600	200	1000	200	20D	10D
04	4.0	22	600	200	1000	200	20D	10D
06	4.0	23	600	200	1000	200	20D	10D
08	5.0	27	600	200	1000	200	20D	10D
10	5.0	30	600	200	1000	200	20D	10D
12	6.0	35	600	200	1000	200	20D	10D
24	8.3	46	600	200	1000	200	20D	10D

Productvoordelen

1. de dirigent is gemaakt van topkwaliteit optische vezels, het heeft lage dispersie en demping, ervoor moet zorgen dat een zeer goed signaal en data transmissie.



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.