



紧套光纤
Tight buffer fiber

芳纶
Aramid yarn

子单元护套
Subunit Jacket

LSZH护套
LSZH Jacket

非金属加强芯
FRP strength member



Kenmerken van het product

1. Multi kabelontwerp
2. Multi kabel elke kabel met onafhankelijke sterkte lid
3. 2 ~ 144 kernen
4. niet-metalen centrale kracht lid

Product toepassing

Aangenomen binnen niveau en verticale leggen, plafond leggen, oppervlakte leggen, enz. Geschikt voor patch snoeren en pigtaills.

De parameter product (meer informatie kunt u mailen naar: info@himakecable.com)

Kabel kern	Buitenste Verwarmingselement (mm)	Gewicht (kg/km)	Min. toegestane treksterkte (N)		Min. toegestane Crush belasting (N / 100mm)		Min. Buigen van Radius (mm)	
			Korte termijn	Lange termijn	Korte termijn	Lange termijn	Korte termijn	Lange termijn
12	15,5	205	1500	500	1500	600	20D	10D
24	15,5	205	1500	500	1500	600	20D	10D
36	17,5	255	1500	500	1500	600	20D	10D
48	17,5	255	1500	500	1500	600	20D	10D
60	19,5	320	1500	500	1500	600	20D	10D
72	19,5	320	1500	500	1500	600	20D	10D
96	22	395	1500	500	1500	600	20D	10D
144	28	597	1500	500	1500	600	20D	10D

Productvoordelen

1. de dirigent is gemaakt van topkwaliteit optische vezels, het heeft lage dispersie en demping, ervoor moet zorgen dat een zeer goed signaal en data transmissie.



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.