

Product Description



The fibers, 250um, are positioned in a loose tube made of a high modulus plastic. The tubes are filled with a water resistant filling compound. A steel wire, sometimes sheathed with PE for cable with high fiber count, locates in the center of core as a metallic strength member. Tubes (and fillers) are stranded around the strength member into a compact and circular cable core. The PSP is longitudinally applied over the cable core, which is filled with the filling compound to protect it from water ingress. The cable is completed with a PE sheath.

Standard: YD/T 901-2001, IEC60794-1

Product characteristics

1. 2~228 fibers, jelly filled, fiber contained loose tubes
2. Good mechanical and temperature performance
3. High strength loose tube that is hydrolysis resistant

4. Special tube filling compound ensure a critical protection of fiber
5. Specially designed compact structure is good at preventing loose tubes from shrinking
6. Crush resistance and flexibility
7. PE sheath protects cable from ultraviolet radiation
8. Good cable watertight.

Product application

Laying modes: Aerial & Conduit

Adopted to outdoor distribution

Long distance and local area network communication

Product parameter (more details please email us: info@himakecable.com)

Fiber count	Cable dia. (mm)	Cable net weight (Kg/km)	Min. bending radius (mm)		Allowable tension (N)		Max. crush loading force (N/1000mm)	
			Static state	Dynamic state	Short term	Long term	Short term	Long term
2-30	9.8	115	10D	20D	1500	600	1000	300
32-36	10.6	140	10D	20D	1500	600	1000	300
38-60	11.0	140	10D	20D	1500	600	1000	300
62-72	11.6	165	10D	20D	1500	600	1000	300
74-96	13.2	205	10D	20D	1500	600	1000	300