



www.himakecable.com
info@himakecable.com

Product Description:

Conductor: Bare Copper

Conductor size: 0.32mm, 0.4mm, 0.5mm, 0.6mm, 0.7mm, 0.9mm

Insulation: HDPE

Cores: 5~2400 pairs, 100 pair and above has the 1% prepared line pairs that is not more than 6 pairs

Insulation color: there is 10 kinds color in total, every pair's insulation color is according to stated chromatogram

Wrapping tape: polyester tape

Shield: Aluminum band, both sides of the aluminum band combine the polyolefin membranes with thickness 0.05mm

Self-support wire: steel wire

Sheath: LDPE

Sheath color: black, or other as per requirement

Package: 100 meters per roll, 500 meters per wooden reel, wooden drum or as per requirement

Main product model: HYA

Product standard: GY/T 322, IEC 708-1, PEA PE-22


Product application:

It is aerial communication cable, applicable to the transmission of analogue signal with audio frequency 150KHZ or less, and the transmission of digital signal of 2048Kbits/s or less, also the digital signal of above


2048Kbits/s in special condition.


Product Electrical Property: (more spec. details please email us: info@himakecable.com)

Cores & Conductor size (mm)	Approx. OD of main cable (mm)	Approx. OD of secondary cable (mm)	Approx. cable weight (kg/km)
10×2×0.40	21	9	335
15×2×0.40	22	10	342
20×2×0.40	23	10	357
25×2×0.40	23	11	382
30×2×0.40	24	12	402
50×2×0.40	25	14	461
100×2×0.40	30	18	640
150×2×0.40	33	21	848
200×2×0.40	36	24	1012



海迈电缆
Himake Cable





CCC CE SAA UL CB RoHS

www.himakecable.com
info@himakecable.com

