

Do you want a good life? Do you want HD view? What are you waiting for? A good horse matches a good saddle, CLEARER VIEW NEEDS HIMAKE CABLES!



Product Description:



Conductor: Bare Copper/CCS

Conductor size: 2.73mm

Dielectric: FPE, SPE

Shield: Aluminum foil + Braiding

Braiding: Al-Mg alloy wire or Tinned copper or Aluminum wire or Bare copper wire

Coverage: 28%, 40%, 60%, 80%, 90% and up

Jacket: PVC / LSZH compound

Jacket color: black, white, grey, or other as per requirement

Package: 100 meters per roll, 305 meters per wooden reel, 500 meters per wooden reel, or as per requirement

Main product model: RG8

Product standard: GY/T 135

Product application

Used as a distribution cable for indoor CATV, CCTV systems and as a connection cable for satellite systems where lower attenuation required.

Application



www.himakecable.com
info@himakecable.com













Product parameter (more details please email us: info@himakecable.com)

Shield type	Standard Shield
Unit	mm
Nominal Conductor Diameter	2.73 BC/CCS
Nominal Diameter Over Dielectric	7.30
Shield structure	Al. Foil + TC/Cu/CCA/Al-Mg alloy wire braiding
Nominal Diameter Over Jacket	10.2



Product Advantages:

1. The product is made of **good quality copper and other raw material**, ensuring a good electrical properties and a very good conductivity.



Traditional PVC Cable	ROHS Cable
 <p>Easy to ageing , Fire risk .</p>	 <p>Using ROHS material , High-tech processing .Life time more than 50 years</p>
 <p>Poor flame retardancy,Fire spread and pop black HCL smoke . 95% fire because of this .</p>	 <p>Good flame retardancy, No fire spread pop a little white smoke after forced burning .</p>
 <p>slow release carcinogenic plasticizer in using , affect health.</p>	 <p>ROHS material , no any environmental issue.</p>
 <p>There are a lots of phthalate , affect children health .No use in Europe .</p>	 <p>Never add any phthalate .</p>
 <p>Lower melting poing .Melting in high temperature.</p>	 <p>Higher melting poing . normally 125°C .</p>
 <p>Easy overload , Melt as soon as catch fire.</p>	 <p>Long term carrying capacity higher than PVC cable 50% ..</p>

2. We are a very **professional cable manufacturer** with advanced production equipments and strict quality inspection system, ensuring the products complying the standard and customized requirement.

□No	★Production Process	□No	★Production Process	□No	★Production Process
1	 Cable Core Shaping	2	 Pair Twisting	3	 Cable Shaping
4	 Braiding Cable	5	 Cable Insulation	6	 Cable Sheathing
7	 Cable Rolling	8	 Cable Inspection	9	 Packing

3. We have more than **10 years' export experience** and exported products to **more than 60 countries** over the world with a good reputation internationally.





305m/pull out box



colour pull out box



2boxes in carton



305m/wooden reel



1000ft/wooden reel



305m wooden reel in carton



warehouse



warehouse



shipment

4. Also we are a company with **highly social responsibility**, often take part in public benefits activities, like tree planting, green environment activities, aiding poor students and the people in difficult condition to achieve their dreams,etc.



How to contact us?

Put your [inquiry details](#) in **the box below**, and click "**Contact Now**".