

Product Description:



China original flexible screened cable CY 300/500V

Nominal Voltage: 300/500V

Conductor: plain annealed copper, tinned copper

Conductor nominal cross section area: 0.50~6.0sqmm

Cores: 2C~61C

Insulation: PVC, flame retardant PVC

Insulation color: white, black, yellow, Red, Blue, Brown, Grey, Green/yellow or other color requested or with figure

Shield: copper wire or tinned copper wire braiding screen

Sheath: PVC, flame retardant PVC

Sheath color: black, white, grey, or as per requirement

Max. operating temperature: 70°C, 90°C

Package: 100 meters per roll, wooden drum, or as per requirement

Main product model: SY control cable

Product standard: IEC60277, BS6500, VDE0250

Product characteristics:

High temperature resistance, low temperature resistance, flame retardant and high electrical conductivity, also fire resistance, UV resistance or RoHS compliant can be available as per request.

Product application:

CY PVC Control Flexible Cable is supplied to a wide number of industries including building and construction (often in airports), rail and transport infrastructure, transmission, distribution and power networks as well as automation and process control. SY Cable is used as interconnecting cable for measuring, controlling or regulation in signal and control equipment.

Product parameter: (more details please email us: info@himakecable.com)

No. of Cores x Nominal Cross Sectional Area	DIAMETER OF BEDDING	DIAMETER OF BRAID	Nominal Overall Diameter	Nominal Cable Weight
No X MM2	MM	MM	mm	kg/km
2 x 0.5	5.5	6.5	8.3	91
3 x 0.5	5.7	6.7	8.6	99
4 x 0.5	6.2	7.2	9.1	113
5 x 0.5	6.7	7.7	9.7	129
7 x 0.5	7.3	8.3	10.3	150
12 x 0.5	9.7	10.7	12.4	214
18 x 0.5	11.2	12.4	14.3	298
25 x 0.5	13.7	14.9	16.8	400
30 x 0.5	14.2	15.4	17.7	454
35 x 0.5	15.9	17.1	19.9	585
41 x 0.5	17.5	18.7	21.5	671
50 x 0.5	18.4	19.6	21.9	694
60 x 0.5	20	21.2	24.2	895
2 x 0.75	6.1	7.1	9	85
3 x 0.75	6.4	7.4	9.3	116
4 x 0.75	6.9	7.9	9.8	133
5 x 0.75	7.6	8.6	10.5	155
7 x 0.75	8.3	9.3	11.2	182
12 x 0.75	10.8	11.8	13.7	266
18 x 0.75	13.1	14.3	16.2	388
25 x 0.75	15.6	16.8	19.1	521
30 x 0.75	16.1	17.3	19.6	572
35 x 0.75	17.9	19.1	21.4	684
50 x 0.75	20.9	22.1	24.8	909
60 x 0.75	22.3	23.8	26.4	1050

Product Advantages:

1. The conductor is made of **new pure annealed copper**, ensuring a good electrical properties and a very good conductivity.



2. We are a very **professional cable manufacturer** with advanced production equipments and strict quality inspection system, ensuring the products complying the standard and customized requirement.

Production equipments



Products Quality inspection equipments



3. We have more than **10 years' export experience** and exported products to **more than 60 countries** over the world with a good reputation internationally.







4. We not only offer **good products** and **good service** to our customers, but also try to **develop our staffs**, offer a good training, good working and living conditions to the staffs.



5. Also we are a company with **highly social responsibility**, often take part in public benefits activities, like tree planting, green environment activities, aiding poor students and the people in difficult condition to achieve their dreams,etc.



