

Product characteristics

- 1. Two single fiber as basic unit, flat twin configuration
- 2. High strength kevlar yarn member, light weight
- 3. High quality tight buffered or loose tube, soft, easy to strip, stainless steel armored flexible tube is optional for armored type, increase the cable's twist resistance, to prevent external damage
- 4. Outer sheath material: PVC, LSZH, OFNP, PU

Product application

Adopted to indoor distribution and communication equipments, suitable for patch cords and pigtails, suitable for communication equipment served

Product parameter (more details please email us: info@himakecable.com)

| Outer | Tight buffer | Weight | Min. allowable Tensile | | Min. allowable Crush | | Min. Bending Radius | |
|---------|--------------|---------|------------------------|-----------|----------------------|-----------|---------------------|-----------|
| Dia. | Dia. | | strength (N) | | Load (N/100m) | | (mm) | |
| (mm) | (mm) | (kg/km) | Short term | Long term | Short term | Long term | Short term | Long term |
| 1.6x3.4 | 0.6 | 4.80 | 150 | 80 | 500 | 100 | 20D | 10D |
| 1.8x3.8 | 0.6 | 5.00 | 150 | 80 | 500 | 100 | 20D | 10D |
| 2.0x4.2 | 0.9 | 7.00 | 150 | 80 | 500 | 100 | 20D | 10D |
| 2.4x5.0 | 0.9 | 9.00 | 150 | 80 | 500 | 100 | 20D | 10D |
| 2.8x5.8 | 0.9 | 11.50 | 150 | 80 | 500 | 100 | 20D | 10D |
| 3.0x6.2 | 0.9 | 12.50 | 150 | 80 | 500 | 100 | 20D | 10D |

(Armored type)

| Outer | Tight buffer | Weight | Min. allowable Tensile | | Min. allowable Crush | | Min. Bending Radius | |
|---------|--------------|---------|------------------------|-----------|----------------------|-----------|---------------------|-----------|
| Dia. | Dia. | | strength (N) | | Load (N/100m) | | (mm) | |
| (mm) | (mm) | (kg/km) | Short term | Long term | Short term | Long term | Short term | Long term |
| 2.0x4.2 | 0.60 | 31 | 1000 | 300 | 1000 | 500 | 20D | 10D |
| 2.4x5.0 | 0.60 | 32 | 1000 | 300 | 1000 | 500 | 20D | 10D |
| 2.8x5.8 | 0.60 | 35 | 1000 | 300 | 1000 | 500 | 20D | 10D |
| 3.0x6.2 | 0.60 | 36 | 1000 | 300 | 1000 | 500 | 20D | 10D |

Product Advantages

1. The conductor is made of Top quality optical fibers, it has Low dispersion and attenuation, ensuring a very good signal and data transmission ability.



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- Long and stability transmission
- > Low Attenuation.





High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.









Optic Fiber Cable Testing

- · Fiber Testing
- · Testing after fiber coloring
- · Testing after fiber stranding
- · Testing after fiber optic cable jacketing



APPLICATION







Pipeline

Overhead

✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



 Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.