



www.himakecable.com
info@himakecable.com

Product characteristics

1. Filler protect tube fiber, E-glass member potentiate
2. Small cable size, light weight
3. 2~24 cores
4. Outer sheath material: PVC, LSZH, PE

Product application

Adopted to indoor or outdoor distribution, suitable for indoor or outdoor aerial, and pipeline performance.

Product parameter (more details please email us: info@himakecable.com)

Cable core count	Outer Dia. (mm)	Weight (kg/km)	Min. allowable Tensile strength (N)		Min. allowable Crush Load (N/100mm)		Min. Bending Radius (mm)	
			Short term	Long term	Short term	Long term	Short term	Long term
02	6.0	45	600	200	1000	200	20D	10D
04	6.0	45	600	200	1000	200	20D	10D
06	6.0	45	600	200	1000	200	20D	10D
08	6.0	45	600	200	1000	200	20D	10D
12	6.0	45	600	200	1000	200	20D	10D

Product Advantages

1. The conductor is made of Top quality optical fibers, it has Low dispersion and attenuation, ensuring a very good signal and data transmission ability.



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.