Product Description:



Conductor: BC

Conductor size: 0.57mm, 23AWG

Twistpairs: 4 pairs

Insulation: PE, HDPE

Insulation color: 4 pairs color: Blue/white-blue; Green/white-green;Orange/white-orange; Brown/white-

brown, color codedaccording to ANSI/TIA/EIA-568-B color code

Shield: Aluminum foil + drain wire + Al-Mg alloy wires screen/copper wire screen/tinned wire screen

shield

Sheath: flame retardant PVC Rohs compliant, LSZH compound

Sheath color: white, grey, blue or as perrequest

Package: 305 meters per box or as perrequirement

Main product model: SFTP Cat6, HSYVP6, HSYYP6, HSYZP6

Product standard: ISO/IEC11801, IEC61156-2,YD/T1019-2001, ANSI/TIA/EIA-568B, UL444

Product characteristics:

UV resistance and Rohscompliant; Feature different strand lay-length, keeping good NEXT and FEXT, antielectromagnetic disturbing improvement; Structure CCS+CCA/CCU/BCconductor, HDP/PE insulation, FRPVC/LSOH PVC jacket, twinning structure, flexible added, easily cabling; High-performance data transmission.


Product application:

The cables transmission frequency up to 250MHz, used as cabling among the cross-connecting box and the communication output and of the operation area or between main distribution frames in the commercial building comprehensive wiring system and residential comprehensive wiring system, support 10Base-T, ISDN, 4.16Mbps TokenRing(IEEE802.5), 1Gbps Ethernet (IEEE802.3), 100Mbps TP-PMD, 100BASE-T4/TX(FASTEthernet), 100VG-AnyLAN Fast Ethernet, 1000Base-T Gigabit Ethernet, 1000Base-TXGigabit Ethernet, 155Mbps ATM, 622Mbps ATM.

Specification datas: (more details please email us: info@himakecable.com)


Product	Norminal Cross-	Wire core	Insulationl	Calculation Outer	Product prox.
Туре	section	Structure	Diameter	Diameter	Weight
Describtion	(mm)	(No./mm)	(mm)	(mm)	(Kg/km)
Cat.6 SFTP PVC	4x2x0.57(23AWG)	1/0.57	1.02	7.8	68
Cat.6 SFTP LSZH	4x2x0.57(23AWG)	1/0.57	1.02	7.8	71
























Packaging & Shipping



How to contact us?

Put your inquiry details in the box below, and click "Contact Now".