Product Description



Nominal Voltage: 3.6/6KV,6/6KV,6/10KV,8.7/10KV,8.7/15KV,12/20KV,18/30KV,21/35KV,26/35KV

Conductor: class 2 strand conductor, pure annealed copper

Conductor nominal cross section area: 25~1000sqmm

Insulation: XLPE

Insulation color: nature color or as request

Shield: Conductor semi-conducting screen + Insulation semi-conducting screen + Metallic screen

Sheath: PVC, flame retardant PVC, Rohs compliant PVC

Sheath color: black or as per request

Max. operating temperature: 90°C

Package: wooden drum or as per requirement

Main product model: YJV, YJV62,YJV72

Product standard: IEC60502, BS6622, VDE0276, GB/T12706, IEC60332

Product characteristics:

High temperature resistance and low temperature resistance, flame retardant and high electrical conductivity, also fire resistance, UV resistance or Rohs compliant can be available as per request.

Product application:

It applies to the transmission and distribution lines with rated voltage up to 26/35 kilovolts, while flame retardant power cable is used in the places with special demands of flame retardant property , where cable is laid tightly.

Product parameter: (more details please email us: info@himakecable.com)

| Cross | XLPE Insulation | Approx. Outer | Approx. ampacity in | Approx. | Approx. |
|--------------------|-----------------|---------------|---------------------|--------------------|---------|
| Section | thickness | diameter | air (A) | ampacity in ground | weight |
| (mm ²) | (mm) | (mm) | | (A) | (Kg/Km) |
| 50 | 4.5 | 24.2 | 245 | 225 | 952 |
| 70 | 4.5 | 26.1 | 305 | 275 | 1190 |
| 95 | 4.5 | 27.7 | 370 | 330 | 1461 |
| 120 | 4.5 | 29.3 | 430 | 375 | 1738 |
| 150 | 4.5 | 30.9 | 490 | 425 | 2054 |
| 185 | 4.5 | 32.7 | 560 | 480 | 2427 |
| 240 | 4.5 | 35.1 | 665 | 555 | 3001 |
| 300 | 4.5 | 37.3 | 765 | 630 | 3604 |
| 3×50 | 4.5 | 51 | 178 | 218 | 3265 |
| 3×70 | 4.5 | 54.8 | 246 | 266 | 4014 |
| 3×95 | 4.5 | 58.5 | 267 | 318 | 4898 |
| 3×120 | 4.5 | 61.7 | 308 | 361 | 5767 |
| 3×150 | 4.5 | 65.3 | 335 | 406 | 6833 |
| 3×185 | 4.5 | 69 | 394 | 461 | 8040 |
| 3×240 | 4.5 | 74.1 | 465 | 529 | 9945 |
| 3×300 | 4.5 | 79.1 | 528 | 593 | 11863 |

Product Advantages:

1. The conductor is made of **new pure annealed copper**, ensuring a good electrical properties and a







| 2. We are a very professional cable manufacturer with advanced production equipments and strict quality inspection system, ensuring the products complying the standard and customized requirement. |
|--|
| Production equipments |
| |
| |
| |
| |
| |
| |

















Products Quality inspection equipments



3. We have more than **10 years' export experience** and exported products to **more than 60 countries** over the world with a good reputation internationally.





4.We not only offer **good products** and **good service** to our customers, but also try to **develop our staffs**, offer a good trainning, good working and living conditions to the staffs.



5. Also we are a company with **highly social reponsibility**, often take part in public benifits activities, like tree planting, aiding poor students, green environment activities, etc.



Put your inquiry details in the box below, and click "Contact Now".