Product Description:



Conductor: CCS+CCA/CCA/CCU/BC

Conductor size: 0.51mm, 24AWG

Twist pairs: 4~25 pairs

Insulation: PE, HDPE

Insulation color: 4 pairs color: Blue/white-blue; Green/white-green; Orange/white-orange; Brown/white-brown, color coded according to ANSI/TIA/EIA-568-B color code

Shield: Aluminum foil + Copper wire screen/tinned copper wire screen shield

Sheath: flame retardant PVC Rohs compliant, LSZH compound

Sheath color: white, grey, blue or as per request

Package: 305 meters per box or as per requirement

Main product model: SFTP Cat5e, HSYVP5e, HSYZP5e

Product characteristics:


UV resistance and Rohs compliant; Feature different strand lay-length, keeping good NEXT and FEXT, antielectromagnetic disturbing improvement; Structure CCS+CCA/CCA/CCU/BC conductor, HDP/PE insulation, FRPVC/LSOH PVC jacket, twinning structure, flexible added, easily cabling; High-performance data transmission.

Product application:

The cables transmission frequency up to 100MHz, used as cabling among the cross-connecting box and the communication output and of the operation area or between main distribution frames in the commercial building comprehensive wiring system and residential comprehensive wiring system, support 10Base-T, ISDN, Token Ring (IEEE 802.5), 100BASE-T4/TX(FAST Ethernet), 100VG-AnyLAN Fast Ethernet, 1000Base-T Gigabit Ethernet, 1000Base-TX Gigabit Ethernet, ATM52/155Mbps, 622Mbps.

Packae datas: (more details please email us: info@himakecable.com)

Product	Norminal Cross-	Wire core	Insulationl	Calculation Outer	Product prox.
Туре	section	Structure	Diameter	Diameter	Weight
Describtion	(mm)	(No./mm)	(mm)	(mm)	(Kg/km)
Cat.5e SFTP PVC	4x2x0.5(24AWG)	1/0.517	1.06	6.2	65
Cat.5e SFTP LSZH	4x2x0.5(24AWG)	1/0.517	1.06	6.2	67





How to contact us?

Put your inquiry details in the box below, and click "Contact Now".