Product Description:



Conductor: CCS+CCA/CCA/CCU/BC

Conductor size: 0.57mm, 23AWG

Twist pairs: 4~25 pairs

Insulation: PE, HDPE

Insulation color: 4 pairs color: Blue/white-blue; Green/white-green; Orange/white-orange; Brown/white-brown, color coded according to ANSI/TIA/EIA-568-B color code

Shield: Aluminum foil for individual pair+ drain wire + copper wire screen/tinned wire screen overall shield

Sheath: flame retardant PVC Rohs compliant, LSZH compound

Sheath color: white, grey, blue or as per request

Package: 305 meters per box or as per requirement

Main product model: SFTP Cat7, HSYVP7, HSYYP7, HSYZP7

Product standard: ISO/IEC11801, IEC61156-2, YD/T1019-2001, ANSI/TIA/EIA-568B, UL444




UV resistance and Rohs compliant; Feature different strand lay-length, keeping good NEXT and FEXT, antielectromagnetic disturbing improvement; Structure CCS+CCA/CCA/CCU/BC conductor, HDP/PE insulation, FRPVC/LSOH PVC jacket, twinning structure, flexible added, easily cabling; High-performance data transmission.

Product application:

The cables transmission frequency up to 600MHz, used as cabling among the cross-connecting box and the communication output and of the operation area or between main distribution frames in the commercial building comprehensive wiring system and residential comprehensive wiring system, support 10GBase-T, 1000BASE-Tx Gigabit Ethernet, 10BASE-T, 100BASE-T fast Ethernet(IEEE 802.3), 100VG-AnyLAN (IEEE802.12), 155/622 Mbps ATM, 550 MHz Broadband Video, Voice, T1, ISDN

Specification datas: (more details please email us: info@himakecable.com)

Product	Norminal Cross-	Wire core	Insulationl	Calculation Outer	Product prox.
Туре	section	Structure	Diameter	Diameter	Weight
Describtion	(mm)	(No./mm)	(mm)	(mm)	(Kg/km)
Cat.7 SFTP PVC	4x2x0.57(23AWG)	1/0.57	1.02	7.8	68
Cat.7 SFTP LSZH	4x2x0.57(23AWG)	1/0.57	1.02	7.8	71





How to contact us?

Put your inquiry details in the box below, and click "Contact Now".