



Tight Buffer Fiber

Aramid Yarn

Subunit Jacket

Jacket

FRP Strength Member



[www.himakecable.com](http://www.himakecable.com)  
[info@himakecable.com](mailto:info@himakecable.com)

## Características de produto

1. Multi cabo único de design
2. único cabo com membros de força independente
3. 2 ~ 24 núcleos
4. membro de força central metaloide

## Aplicação do produto

Adotou a postura interior de horizontal e vertical, que fixa teto, imposição de superfície, etc. Apropriado para os cabos de remendo e rabo de cavalo.

**Parâmetro de produto** (mais detalhes envie um email: [info@himakecable.com](mailto:info@himakecable.com))

Ccapaz núcleo	Exterior Dia.	Peso	Min. resistência à tração permissível (N)		Min. Carga de esmagar admissível (N / 100mm)		Min. Raio de curvatura (mm)	
			Curta termo	Longas termo	Curta termo	Longas termo	Curta termo	Longas termo
02	7.0	45	1500	500	1000	300	20D	10-D
04	7.0	47	1500	500	1000	300	20D	10-D
06	8.3	64	1500	500	1000	300	20D	10-D
08	9.5	88	1500	500	1000	300	20D	10-D
12	11.5	105	1500	500	1000	300	20D	10-D
24	13.5	142	1500	500	1000	300	20D	10-D

## Vantagens do produto

1. o condutor é feito de fibras ópticas de alta qualidade, tem baixa dispersão e atenuação, garantindo uma capacidade de transmissão de dados e sinal muito bom.



### **Brand new material**

- > **Smooth**
- > **Anti-UV**
- > **Long-life**

### **High Quality Fiber**

- > **Fast**
- > **Long and stability transmission**
- > **Low Attenuation.**



### **High Quality PBT Loose Tube Material**

- > **Anti-aging**
- > **Good Protection**

# ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



## Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



## APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

### Packaging & Shipping

## PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.