

Características de produto

- 1. Multi cabo único de design
- 2. único cabo com membros de força independente
- 3. 2 ~ 24 núcleos
- 4. membro de força central metaloide

Aplicação do produto

Adotou a postura interior de horizontal e vertical, que fixa teto, imposição de superfície, etc. Apropriado para os cabos de remendo e rabo de cavalo.

Parâmetro de produto (mais detalhes envie um email: info@himakecable.com)

Ccapaz núcleo	Exterior Dia.	Peso					Min. Raio de curvatura (mm)	
contagem	(mm)	(kg\/km)	Curta termo	Longas termo	Curta termo	Longas termo	Curta termo	Longas termo
02	7.0	45	1500	500	1000	300	20D	10-D
04	7.0	47	1500	500	1000	300	20D	10-D
06	8.3	64	1500	500	1000	300	20D	10-D
08	9.5	88	1500	500	1000	300	20D	10-D
12	11.5	105	1500	500	1000	300	20D	10-D
24	13.5	142	1500	500	1000	300	20D	10-D


Vantagens do produto

1. o condutor é feito de fibras ópticas de alta qualidade, tem baixa dispersão e atenuação, garantindo uma capacidade de transmissão de dados e sinal muito bom.



Brand new material

- > Smooth
- > Anti-UV
- > Long-life



- > Fast
- > Long and stability transmission
- > Low Attenuation.





High Quality PBT Loose
Tube Material

- > Anti-aging
- Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.









Optic Fiber Cable Testing

- · Fiber Testing
- · Testing after fiber coloring
- · Testing after fiber stranding
- · Testing after fiber optic cable jacketing



APPLICATION







Pipeline

Overhead

✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



 Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.