

Product Description:
Conductor: Bare Copper/TC
Conductor size: 0.4mm, 0.5mm, 0.6mm, 0.8mm
Insulation: PE
Cores: 2C, 4C,6C, 8C, or 1~4 pairs for indoor use, 5~200 pairs for outdoor use mainly
Shield (optional): drain wire + Al foil + braiding (optional)
Sheath: PVC or LDPE
Sheath color: black, white, grey, or other as per requirement
Package: 100 meters per roll, 200 meters per roll, 500 meters per wooden reel, or as per requirement
Main product model: HYV, HYY, HYVP
Product standard: GY/T 840, GY/T 322, ISO/IEC 11801, ANSL/EIA/TIA 568B

Product application:
Used for the connection between floor cabling system in the telephone communication cabling system and the user's telephone outlet, used for the interconnection between telephone exchange and extension sets and between other communication equipments, also used for terminal telephones, faxes, digital telephones, visual building telecom system. Shielded cable should be used in the cabling system in areas with serious interference.

Product Electrical Property: (more spec. details please email us: info@himakecable.com)

Conductor diameter	0.50mm	0.60mm	0.80mm
DC resistance Ω/km 20℃	≤95	≤65.8	≤36.6
DC resistance imbalance% 20℃	≤5	≤5	≤5
Insulated dielectric strength	1500ac or 2250ac,mustn't be punched in 1 minute		
The situation of conductor wire breadking and mixing	No breaking or mixing		

海迈电缆
Himake Cable

www.himakecable.com
info@himakecable.com

mm/inch
ZERO
mm
info@himakecable.com