



Características de produto

1. membro de fio de kevlar de de grande resistência
2. mais apertado no buffer do projeto
3. redondo construção, macia, fácil tirar a roupa
4. 2 ~ 48 núcleos
5. material de bainha exterior: PVC, PU LSZH, OFNP

Aplicação do produto

Adotado para distribuição interna, apropriada para conexão de chão, apropriado para o equipamento de comunicação.

Parâmetro de produto (mais detalhes envie um email: info@himakecable.com)

Cabo núcleo contagem	Exterior Dia. (mm)	Peso (kg/km)	Min. resistência à tração permisível (N)		Min. Carga de esmagar admissível (N / 100mm)		Min. Raio de curvatura (mm)	
			Curta termo	Longas termo	Curta termo	Longas termo	Curta termo	Longas termo
02	3.0	15	600	200	1000	200	30%	10-D
04	4.0	22	600	200	1000	200	30%	10-D
06	4.0	23	600	200	1000	200	30%	10-D
08	5.0	27	600	200	1000	200	30%	10-D
10	5.0	30	600	200	1000	200	30%	10-D
12	6.0	35	600	200	1000	200	30%	10-D
24	8.3	46	600	200	1000	200	30%	10-D

Vantagens do produto

1. o condutor é feito de fibras ópticas de alta qualidade, tem baixa dispersão e atenuação, garantindo uma capacidade de transmissão de dados e sinal muito bom.



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.