Características de produto

1. Multi cabo design
2. Multi cabo cada cabo com membros de força independente
3. 2 ~ 144 núcleos
4. membro de força central metaloide

Aplicação do produto

Adotou a postura interior de horizontal e vertical, que fixa teto, imposição de superfície, etc. Apropriado para os cabos de remendo e rabo de cavalo.

Parâmetro de produto (mais detalhes envie um email: info@himakecable.com)

Cabo núcleo	Exterior Dia.	Peso	Min. resistência à tração permissível (N)		Min. Carga de esmagar admissível (N \/ 100mm)		Min. Raio de curvatura (mm)	
contagem	(mm)	(kg\/km)	Curta termo	Longas termo	Curta termo	Longas termo	Curta termo	Longas termo
12	15.5	205	1500	500	1500	600	30%	10-D
24	15.5	205	1500	500	1500	600	30%	10-D
36	17.5	255	1500	500	1500	600	30%	10-D
48	17.5	255	1500	500	1500	600	30%	10-D
60	19,5	320	1500	500	1500	600	30%	10-D
72	19,5	320	1500	500	1500	600	30%	10-D
96	22	395	1500	500	1500	600	30%	10-D
144	28	597	1500	500	1500	600	30%	10-D

Vantagens do produto

1. o condutor é feito de fibras ópticas de alta qualidade, tem baixa dispersão e atenuação, garantindo uma capacidade de transmissão de dados e sinal muito bom.

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.

Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing

APPLICATION

✔ Pipeline

✔ Overhead

✔ Direct bury

Packaging & Shipping

PACKING AND SHIPPING

- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.

info@himakecable.com